



SAFETY DATA SHEET

This safety data sheet was created pursuant to the requirements of:
US OSHA Hazard Communication Standard (29 CFR 1910.1200) and Canada WHMIS
2015 which includes the amended Hazardous Products Act (HPA) and the Hazardous
Products Regulation (HPR)

Revision Date 20-Apr-2026

Version 2

1. Identification

Product identifier

Product Name Wynn's Throttle Body Cleaner

Other means of identification

Product Code WN 58001

Synonyms None

Recommended use of the chemical and restrictions on use

Recommended Use See directions provided with product

Restrictions on use All other applications

Details of the supplier of the safety data sheet

Supplier Address

ITW Professional Automotive Products
3606 Craftsman Blvd.
Lakeland, FL 33803

Distributor

Manufacturer Address

May Also Be Distributed by:

Logistic Distribution
550 Industrial Drive
Milton, ON, Canada L9T 5A6

Manufactured and Distributed by:

Emergency telephone number

Company Phone Number 863-665-3338

24-hour emergency phone number Chem-Tel: 800-255-3924
International Emergency:
00+1+ 813-248-0585
Contract Number: MIS0003583

2. Hazard(s) identification

Classification of the substance or mixture

Aerosols	Category 1
Serious eye damage/eye irritation	Category 2A
Reproductive toxicity	Category 2
Specific target organ toxicity (single exposure)	Category 3
Category 3 Target organ effects: Narcotic effects.	
Specific target organ toxicity (repeated exposure)	Category 2

Label elements

**Danger****Hazard statements**

Extremely flammable aerosol. Pressurized container: May burst if heated.

Causes serious eye irritation.

Suspected of damaging fertility or the unborn child.

May cause drowsiness or dizziness.

May cause damage to organs through prolonged or repeated exposure.

Precautionary Statements - Prevention

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

Wear protective gloves, protective clothing, eye protection and face protection.

Wash face, hands and any exposed skin thoroughly after handling.

Use only outdoors or in a well-ventilated area.

Do not breathe dust.

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Do not pierce or burn, even after use.

Do not spray on an open flame or other ignition source.

Precautionary Statements - Response

IF exposed or concerned: Get medical advice/attention.

Eyes

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

If eye irritation persists: Get medical advice and attention.

Inhalation

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

Call a POISON CENTER or doctor if you feel unwell.

Precautionary Statements - Storage

Store locked up.

Store in a well-ventilated place. Keep container tightly closed.

Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

Precautionary Statements - Disposal

Dispose of contents and container in accordance with local, regional, national, and international regulations as applicable.

7 % of the mixture consists of ingredient(s) of unknown acute oral toxicity.

7 % of the mixture consists of ingredient(s) of unknown acute dermal toxicity.

99.7504 % of the mixture consists of ingredient(s) of unknown acute inhalation toxicity (vapor).

Hazards classified under paragraph (d)(1)(ii) of 1910.1200

No information available.

Other Information

May be harmful if inhaled. Causes mild skin irritation. Harmful to aquatic life with long lasting effects.

3. Composition/information on ingredients**Substance**

Not applicable.

Mixture

Chemical name	CAS No.	Weight-%	Hazardous Material Information Review Act registry number (HMIRA registry #)	Date HMIRA filed and date exemption granted (if applicable)
Acetone	67-64-1	65-85%	-	-
Toluene	108-88-3	5-10%	-	-
CARBON DIOXIDE	124-38-9	5-10%	-	-

4. First-aid measures

Description of first aid measures

General advice	Show this safety data sheet to the doctor in attendance.
Inhalation	Remove to fresh air. IF exposed or concerned: Get medical advice/attention.
Eye contact	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Keep eye wide open while rinsing. Do not rub affected area. Get medical attention if irritation develops and persists.
Skin contact	Wash skin with soap and water.
Ingestion	Do NOT induce vomiting. Rinse mouth. Never give anything by mouth to an unconscious person. Call a physician.
Self-protection of the first aider	Remove all sources of ignition. Ensure that medical personnel are aware of the material(s) involved, take precautions to protect themselves and prevent spread of contamination. Wear personal protective clothing (see section 8). Avoid contact with skin, eyes or clothing.

Most important symptoms and effects, both acute and delayed

Symptoms	May cause redness and tearing of the eyes. Burning sensation. Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting. Prolonged contact may cause redness and irritation.
Effects of Exposure	May cause adverse reproductive effects - such as birth defect, miscarriages, or infertility. May cause damage to organs through prolonged or repeated exposure.

Indication of any immediate medical attention and special treatment needed

Note to physicians	Treat symptomatically.
--------------------	------------------------

5. Fire-fighting measures

Suitable Extinguishing Media	Dry chemical. Carbon dioxide (CO2). Water spray.
Large Fire	CAUTION: Use of water spray when fighting fire may be inefficient.
Unsuitable extinguishing media	DO NOT EXTINGUISH A LEAKING GAS FIRE UNLESS LEAK CAN BE STOPPED.
Specific hazards arising from the chemical	Risk of ignition. Keep product and empty container away from heat and sources of ignition. In the event of fire, cool tanks with water spray. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations. Cylinders may rupture under extreme heat. Damaged cylinders should be handled only by specialists. Containers may explode when heated.

Explosion data

Sensitivity to mechanical impact None.

Sensitivity to static discharge Yes.

Special protective equipment and precautions for fire-fighters

Firefighters should wear self-contained breathing apparatus and full firefighting turnout gear. Use personal protection equipment.

6. Accidental release measures**Personal precautions, protective equipment and emergency procedures****Personal precautions**

Evacuate personnel to safe areas. Use personal protective equipment as required. See section 8 for more information. Avoid contact with skin, eyes or clothing. Ensure adequate ventilation. Keep people away from and upwind of spill/leak. ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Take precautionary measures against static discharges. Avoid breathing dust/fume/gas/mist/vapors/spray.

Other information

Ventilate the area. Refer to protective measures listed in Sections 7 and 8.

Methods and material for containment and cleaning up**Methods for containment**

Stop leak if you can do it without risk. A vapor suppressing foam may be used to reduce vapors. Dike far ahead of spill to collect runoff water. Keep out of drains, sewers, ditches and waterways. Flood with water to complete polymerization and scrape off floor.

Methods for cleaning up

Take precautionary measures against static discharges. Dam up. Soak up with inert absorbent material. Pick up and transfer to properly labeled containers.

Prevention of secondary hazards

Clean contaminated objects and areas thoroughly observing environmental regulations.

7. Handling and storage**Precautions for safe handling****Advice on safe handling**

Use personal protection equipment. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapors). Use spark-proof tools and explosion-proof equipment. Handle product only in closed system or provide appropriate exhaust ventilation. Keep in an area equipped with sprinklers. Do not puncture or incinerate cans. Contents under pressure. In case of rupture. Avoid breathing vapors or mists. Handle in accordance with good industrial hygiene and safety practice. Avoid contact with skin, eyes or clothing. Do not eat, drink or smoke when using this product. Remove contaminated clothing and shoes. In case of insufficient ventilation, wear suitable respiratory equipment.

Conditions for safe storage, including any incompatibilities**Storage Conditions**

Protect from sunlight. Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric motors and static electricity). Keep in properly labeled containers. Do not store near combustible materials. Keep in an area equipped with sprinklers. Store in accordance with the particular national regulations. Store in accordance with local regulations. Store in a cool, dry area away from potential sources of heat, open flames, sunlight or other chemicals. Store locked up.

8. Exposure controls/personal protection

Control Parameters**Exposure Limits**

Chemical name	ACGIH TLV	OSHA PEL	NIOSH
Acetone 67-64-1	TWA: 250 ppm STEL: 500 ppm	TWA: 1000 ppm TWA: 2400 mg/m ³ (vacated) TWA: 750 ppm (vacated) TWA: 1800 mg/m ³ (vacated) STEL: 2400 mg/m ³ The acetone STEL does not apply to the cellulose acetate fiber industry. It is in effect for all other sectors. (vacated) STEL: 1000 ppm	TWA: 250 ppm; TWA: 590 mg/m ³ ; IDLH: 2500 ppm
Toluene 108-88-3	TWA: 20 ppm pOt	TWA: 200 ppm (vacated) TWA: 100 ppm (vacated) TWA: 375 mg/m ³ (vacated) STEL: 150 ppm (vacated) STEL: 560 mg/m ³ Ceiling: 300 ppm	TWA: 100 ppm; TWA: 375 mg/m ³ ; STEL: 150 ppm STEL: 560 mg/m ³ IDLH: 500 ppm
CARBON DIOXIDE 124-38-9	TWA: 5000 ppm STEL: 30000 ppm	TWA: 5000 ppm TWA: 9000 mg/m ³ (vacated) TWA: 10000 ppm (vacated) TWA: 18000 mg/m ³ (vacated) STEL: 30000 ppm (vacated) STEL: 54000 mg/m ³	TWA: 5000 ppm; TWA: 9000 mg/m ³ ; STEL: 30000 ppm STEL: 54000 mg/m ³ IDLH: 40000 ppm

Chemical name	Alberta	British Columbia	Ontario	Quebec
Acetone 67-64-1	TWA: 500 ppm; TWA: 1200 mg/m ³ ; STEL: 750 ppm; STEL: 1800 mg/m ³ ;	TWA: 250 ppm; STEL: 500 ppm;	TWA: 250 ppm; STEL: 500 ppm;	TWAEV: 250 ppm; STEV: 500 ppm;
Toluene 108-88-3	TWA: 50 ppm; TWA: 188 mg/m ³ ; pSk	TWA: 20 ppm; Adverse reproductive effect	TWA: 20 ppm;	TWAEV: 20 ppm;
CARBON DIOXIDE 124-38-9	TWA: 5000 ppm; TWA: 9000 mg/m ³ ; STEL: 30000 ppm; STEL: 54000 mg/m ³ ;	TWA: 5000 ppm; STEL: 15000 ppm;	TWA: 5000 ppm; STEL: 30000 ppm;	TWAEV: 5000 ppm; TWAEV: 9000 mg/m ³ ; STEV: 30000 ppm; STEV: 54000 mg/m ³ ;

Chemical name	Manitoba	New Brunswick	Newfoundland and Labrador	Nova Scotia
Acetone	TWA: 250 ppm; STEL: 500 ppm;	TWA: 250 ppm; STEL: 500 ppm;	TWA: 250 ppm; STEL: 500 ppm;	TWA: 250 ppm; STEL: 500 ppm;
Toluene	TWA: 20 ppm;	TWA: 20 ppm;	TWA: 20 ppm;	TWA: 20 ppm;
CARBON DIOXIDE	TWA: 5000 ppm; STEL: 30000 ppm;	TWA: 5000 ppm; STEL: 30000 ppm;	TWA: 5000 ppm; STEL: 30000 ppm;	TWA: 5000 ppm; STEL: 30000 ppm;

Chemical name	Nunavut	Prince Edward Island	Saskatchewan	Yukon
Acetone	TWA: 500 ppm; STEL: 750 ppm;	TWA: 250 ppm; STEL: 500 ppm;	TWA: 500 ppm; STEL: 750 ppm;	TWA: 1000 ppm; TWA: 2400 mg/m ³ ; STEL: 1250 ppm; STEL: 3000 mg/m ³ ;
Toluene	TWA: 50 ppm; STEL: 60 ppm; Sk	TWA: 20 ppm;	TWA: 50 ppm; STEL: 60 ppm; pSd	TWA: 100 ppm; TWA: 375 mg/m ³ ; STEL: 150 ppm;

Chemical name	Nunavut	Prince Edward Island	Saskatchewan	Yukon
				STEL: 560 mg/m ³ ; Sk
CARBON DIOXIDE	TWA: 5000 ppm; STEL: 30000 ppm;	TWA: 5000 ppm; STEL: 30000 ppm;	TWA: 5000 ppm; STEL: 30000 ppm;	TWA: 5000 ppm; TWA: 9000 mg/m ³ ; STEL: 15000 ppm; STEL: 27000 mg/m ³ ;

Biological occupational exposure limits

Chemical name	ACGIH
Acetone 67-64-1	25 mg/L - urine (Acetone) - end of shift
Toluene 108-88-3	0.02 mg/L - blood (Toluene) - prior to last shift of workweek 0.03 mg/L - urine (Toluene) - end of shift 0.3 mg/g creatinine - urine (o-Cresol with hydrolysis) - end of shift

Appropriate engineering controls

Engineering controls	Showers Eyewash stations Ventilation systems.
-----------------------------	---

Individual protection measures, such as personal protective equipment

Eye/face protection	Tight sealing safety goggles.
Hand protection	Wear suitable gloves.
Skin and body protection	Wear suitable protective clothing. Antistatic boots. Chemical resistant apron. Wear fire/flammable resistant/retardant clothing.
Respiratory protection	Use appropriate respiratory protection. Consult with an industrial hygienist to determine the appropriate respiratory protection for your specific use of this material.
General hygiene considerations	Do not eat, drink or smoke when using this product. Contaminated work clothing should not be allowed out of the workplace. Regular cleaning of equipment, work area and clothing is recommended. Wash hands before breaks and immediately after handling the product. Avoid contact with skin, eyes or clothing. Wear suitable gloves and eye/face protection.

9. Physical and chemical properties**Information on basic physical and chemical properties**

Appearance	Liquid Aerosol
Physical state	Aerosol
Color	Colorless
Odor (includes odor threshold)	

<u>Property</u>	<u>Values</u>	<u>Remarks • Method</u>
Melting point / freezing point	No data available	
Boiling point (or initial boiling point or boiling range)	56 °C / 132.8 °F	
Flammability (solid, gas)	No data available	

Flammability Limit in Air	
Upper flammability limit:	2.6
Lower flammability limit:	12.8
Flash point	-20 °C / -4 °F
Autoignition temperature	465 °C / 869 °F
Decomposition temperature	No data available
SADT (°C)	No data available
pH	No data available
pH (as aqueous solution)	No data available
Kinematic viscosity	No Data Available
Dynamic viscosity	No data available
Solubility	No Data Available
Water solubility	Miscible in water
Partition coefficient n-octanol/water (log value)	No Data Available
Vapor pressure (includes evaporation rate)	185
Evaporation rate	14.4
Density and/or relative density	0.798
Bulk density	No data available
Density	0.797 g/cm3
Vapor density	No data available
Particle characteristics	
Particle Size	No data available
Particle Size Distribution	No data available

Other information**10. Stability and reactivity**

Reactivity	No information available.
Chemical stability	Stable under normal conditions.
Possibility of hazardous reactions	None under normal processing.
Conditions to avoid	Heat, flames and sparks.
Incompatible materials	None known based on information supplied.
Hazardous decomposition products	None known based on information supplied.

11. Toxicological information**Information on likely routes of exposure****Product Information**

Inhalation	Intentional misuse by deliberately concentrating and inhaling contents may be harmful or fatal. Specific test data for the substance or mixture is not available. May cause irritation of respiratory tract. May cause drowsiness or dizziness. May be harmful if inhaled.
Eye contact	Specific test data for the substance or mixture is not available. Causes serious eye irritation. (based on components). May cause redness, itching, and pain.
Skin contact	Specific test data for the substance or mixture is not available. Prolonged contact may cause redness and irritation. Causes mild skin irritation.
Ingestion	Specific test data for the substance or mixture is not available. Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea.

Symptoms related to the physical, chemical and toxicological characteristics

Symptoms May cause redness and tearing of the eyes. Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting. Prolonged contact may cause redness and irritation.

Acute toxicity**Numerical measures of toxicity**

The following ATE values have been calculated for the mixture

ATEmix (oral)	6,149.40 mg/kg
ATEmix (dermal)	16,393.10 mg/kg
ATEmix (inhalation-gas)	99,999.00 ppm
ATEmix (inhalation-vapor)	99,999.00 mg/L
ATEmix (inhalation-dust/mist)	62.00 mg/L

7 % of the mixture consists of ingredient(s) of unknown acute oral toxicity

7 % of the mixture consists of ingredient(s) of unknown acute dermal toxicity

99.7504 % of the mixture consists of ingredient(s) of unknown acute inhalation toxicity (vapor)

Component Information

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
Acetone 67-64-1	= 5800 mg/kg (Rat)	> 15700 mg/kg (Rabbit)	= 50100 mg/m ³ (Rat) 8 h
Toluene 108-88-3	= 5000 mg/kg (Rat)	= 12000 mg/kg (Rabbit)	= 12.5 mg/L (Rat) 4 h

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritation Classification based on data available for ingredients. Causes mild skin irritation.

Serious eye damage/eye irritation Classification based on data available for ingredients. Causes serious eye irritation.

Respiratory or skin sensitization No information available.

Germ cell mutagenicity No information available.

Carcinogenicity Based on available data, the classification criteria are not met.

The table below indicates whether each agency has listed any ingredient as a carcinogen.

Chemical name	ACGIH	IARC	NTP	OSHA
Acetone 67-64-1	A4 - Not Classifiable as a Human Carcinogen	-	-	-
Toluene 108-88-3	A4 - Not Classifiable as a Human Carcinogen	Group 3 - Unclassifiable as to carcinogenicity in humans	-	-

Reproductive toxicity Contains a known or suspected reproductive toxin. Classification based on data available for ingredients. Suspected of damaging fertility or the unborn child.

STOT - single exposure May cause drowsiness or dizziness.

STOT - repeated exposure May cause damage to organs through prolonged or repeated exposure.

Aspiration hazard No information available.

12. Ecological information

Ecotoxicity Harmful to aquatic life with long lasting effects.

Chemical name	Algae/aquatic plants	Fish	Toxicity to microorganisms	Crustacea
Acetone 67-64-1	-	LC50: 4.74 - 6.33mL/L (96h, <i>Oncorhynchus mykiss</i>) LC50: 6210 - 8120mg/L (96h, <i>Pimephales promelas</i>) LC50: =8300mg/L (96h, <i>Lepomis macrochirus</i>)	-	EC50: 10294 - 17704mg/L (48h, <i>Daphnia magna</i>) EC50: 12600 - 12700mg/L (48h, <i>Daphnia magna</i>)
Toluene 108-88-3	EC50: >433mg/L (96h, <i>Pseudokirchneriella subcapitata</i>) EC50: =12.5mg/L (72h, <i>Pseudokirchneriella subcapitata</i>)	LC50: 15.22 - 19.05mg/L (96h, <i>Pimephales promelas</i>) LC50: =12.6mg/L (96h, <i>Pimephales promelas</i>) LC50: 5.89 - 7.81mg/L (96h, <i>Oncorhynchus mykiss</i>) LC50: 14.1 - 17.16mg/L (96h, <i>Oncorhynchus mykiss</i>) LC50: =5.8mg/L (96h, <i>Oncorhynchus mykiss</i>) LC50: 11.0 - 15.0mg/L (96h, <i>Lepomis macrochirus</i>) LC50: =54mg/L (96h, <i>Oryzias latipes</i>) LC50: =28.2mg/L (96h, <i>Poecilia reticulata</i>) LC50: 50.87 - 70.34mg/L (96h, <i>Poecilia reticulata</i>)	EC50 = 19.7 mg/L 30 min	EC50: 5.46 - 9.83mg/L (48h, <i>Daphnia magna</i>) EC50: =11.5mg/L (48h, <i>Daphnia magna</i>)

Persistence and degradability No information available.

Bioaccumulative potential

Component Information

Chemical name	Partition coefficient
Acetone 67-64-1	-0.24
Toluene 108-88-3	3.93

Other adverse effects No information available.

13. Disposal considerations

Waste treatment methods

Waste from residues/unused products	Should not be released into the environment. Dispose of in accordance with local regulations. Dispose of waste in accordance with environmental legislation.
Contaminated packaging	Empty containers pose a potential fire and explosion hazard. Do not cut, puncture or weld containers.
US EPA Waste Number	U002 U220
California waste information	This product contains one or more substances that are listed with the State of California as a hazardous waste.

14. Transport information

DOT

UN number or ID number	UN1950
Proper shipping name	Aerosols, Flammable Limited Quantity (LQ)
Transport hazard class(es)	2.1

IATA

UN number or ID number	UN1950
UN proper shipping name	Aerosols, Flammable Limited Quantity (LQ)
Transport hazard class(es)	2.1

IMDG

UN number or ID number	UN1950
UN proper shipping name	Aerosols, Flammable Limited Quantity (LQ)
Transport hazard class(es)	2.1

15. Regulatory information

Safety, health and environmental regulations/legislation specific for the substance or mixture

International Regulations

The Montreal Protocol on Substances that Deplete the Ozone Layer Not applicable

The Stockholm Convention on Persistent Organic Pollutants Not applicable

The Rotterdam Convention Not applicable

*Contact supplier for details. One or more substances in this product are either not listed on the US TSCA inventory, listed on the confidential US TSCA inventory or are otherwise exempted from inventory listing requirements

International Inventories

TSCA	Complies
DSL/NDL	Complies
EINECS/ELINCS	Complies
ENCS	Does not comply
IECSC	Complies

KECI	Does not comply
PICCS	Complies
AICS	Does not comply

Legend:

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory
DSL/NDL - Canadian Domestic Substances List/Non-Domestic Substances List
EINECS/ELINCS - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances
ENCS - Japan Existing and New Chemical Substances
IECSC - China Inventory of Existing Chemical Substances
KECL - Korean Existing Chemicals Inventory
PICCS - Philippines Inventory of Chemicals and Chemical Substances
AICS - Australian Inventory of Chemical Substances

US Federal Regulations**SARA 313**

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372.

Chemical name	SARA 313 - Threshold Values %
Toluene - 108-88-3	1.0

Should this product meet EPCRA 311/312 Tier reporting criteria at 40 CFR 370, refer to Section 2 of this SDS for appropriate classifications.

SARA 311/312 Hazard Categories

Acute health hazard	No
Chronic Health Hazard	No
Fire hazard	Yes
Sudden release of pressure hazard	No
Reactive Hazard	No

CWA (Clean Water Act)

This product contains the following substances which are regulated pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42).

Chemical name	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
Toluene 108-88-3	1000 lb	X	X	X

CERCLA

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302).

Chemical name	Hazardous Substances RQs	Extremely Hazardous Substances RQs	Reportable Quantity (RQ)
Acetone 67-64-1	5000 lb / kg (final RQ)	-	RQ 5000 lb final RQ RQ 2270 kg final RQ
Toluene 108-88-3	1000 lb / 1 lb / kg (final RQ) kg (final RQ)	-	RQ 1000 lb final RQ RQ 454 kg final RQ RQ 1 lb final RQ RQ 0.454 kg final RQ

US State Regulations**California Proposition 65**

This product contains the following Proposition 65 chemicals:

Chemical name	California Proposition 65
Toluene - 108-88-3	Developmental

U.S. State Right-to-Know Regulations

Chemical name	New Jersey	Massachusetts	Pennsylvania
Acetone 67-64-1	X	X	X
Toluene 108-88-3	X	X	X
CARBON DIOXIDE 124-38-9	X	X	X

U.S. EPA Label Information

EPA Pesticide Registration Number Not applicable

WHMIS Hazard Class

Non-controlled

16. Other information

<u>NFPA</u>	Health hazards 2	Flammability 3	Instability 0	Special hazards -
<u>HMIS</u>	Health hazards 2 *	Flammability 3	Physical hazards 0	Personal protection X
<i>Chronic Hazard Star Legend</i>	<i>* = Chronic Health Hazard</i>			

Revision Date 20-Apr-2026

Revision Note No information available.

Disclaimer

Illinois Tool Works Inc. believes the information contained in this data sheet is accurate as of the date compiled. However, Illinois Tool Works Inc. makes no warranty, express or implied, as to the accuracy, reliability or completeness of the information. User is responsible for evaluating whether such information or this product is fit for a particular purpose and suitable for a particular use or application. The information in this data sheet may not be valid if this product is used in combination with other products or in processes for which it was not designed. Illinois Tool Works Inc. disclaims any liability for consequential or incidental damages of any kind, including lost profits, arising from the sale or use of this product. Ensure you have the most current version of this data sheet by contacting us or reviewing our web site.