



SAFETY DATA SHEET

This safety data sheet was created pursuant to the requirements of:
US OSHA Hazard Communication Standard (29 CFR 1910.1200) and Canada WHMIS
2015 which includes the amended Hazardous Products Act (HPA) and the Hazardous
Products Regulation (HPR)

Revision Date 21-Apr-2026

Version 2

1. Identification

Product identifier

Product Name Wynn's Super Concentrated Windshield Washer Solvent

Other means of identification

Product Code WN A5201

Synonyms None

Recommended use of the chemical and restrictions on use

Recommended Use See directions provided with product

Restrictions on use All other applications

Details of the supplier of the safety data sheet

Supplier Address
ITW Professional Automotive Products
3606 Craftsman Blvd.
Lakeland, FL 33803

Manufacturer Address

Manufactured and Distributed by:

Distributor

May Also Be Distributed by:
Logistic Distribution
550 Industrial Drive
Milton, ON, Canada L9T 5A6

Emergency telephone number

Company Phone Number 863-665-3338

24-hour emergency phone number Chem-Tel: 800-255-3924
International Emergency:
00+1+ 813-248-0585
Contract Number: MIS0003583

2. Hazard(s) identification

Classification of the substance or mixture

Flammable liquids	Category 2
Acute toxicity - Oral	Category 3
Acute toxicity - Dermal	Category 3
Acute toxicity - Inhalation (Dusts/Mists)	Category 3
Specific target organ toxicity (single exposure)	Category 1

Label elements



Danger

Hazard statements

Highly flammable liquid and vapor.
Toxic if swallowed.
Toxic in contact with skin.
Toxic if inhaled.
Causes damage to organs.

Precautionary Statements - Prevention

Wash face, hands and any exposed skin thoroughly after handling.
Do not eat, drink or smoke when using this product.
Wear protective gloves, protective clothing, eye protection and face protection.
Use only outdoors or in a well-ventilated area.
Do not breathe dust.
Ground and bond container and receiving equipment.
Use non-sparking tools.
Take action to prevent static discharges.
Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
Keep container tightly closed.
Use explosion-proof electrical, ventilating and lighting equipment.
Keep cool.

Precautionary Statements - Response

Specific treatment (see supplemental first aid instructions on this label).
IF exposed or concerned: Call a POISON CENTER or doctor.

Skin

IF ON SKIN: Wash with plenty of water and soap.
Call a POISON CENTER or doctor if you feel unwell.
Take off immediately all contaminated clothing and wash it before reuse.
IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.

Inhalation

IF INHALED: Remove person to fresh air and keep comfortable for breathing.
Call a POISON CENTER or doctor.

Ingestion

IF SWALLOWED: Immediately call a POISON CENTER or doctor.
Rinse mouth.

Fire

In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.

Precautionary Statements - Storage

Store locked up.
Store in a well-ventilated place. Keep container tightly closed.
Store in a well-ventilated place. Keep cool.

Precautionary Statements - Disposal

Dispose of contents and container in accordance with local, regional, national, and international regulations as applicable.

Unknown acute toxicity

Hazards classified under paragraph (d)(1)(ii) of 1910.1200

No information available.

Other Information

Harmful to aquatic life.

3. Composition/information on ingredients

Substance

Not applicable.

Mixture

Chemical name	CAS No.	Weight-%	Hazardous Material Information Review Act registry number (HMIRA registry #)	Date HMIRA filed and date exemption granted (if applicable)
METHANOL	67-56-1	80-100%	-	-

4. First-aid measures

Description of first aid measures

General advice	Show this safety data sheet to the doctor in attendance. Immediate medical attention is required.
Inhalation	Remove to fresh air. IF exposed or concerned: Get medical advice/attention. If breathing has stopped, give artificial respiration. Get medical attention immediately. Do not use mouth-to-mouth method if victim ingested or inhaled the substance; give artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device. If breathing is difficult, (trained personnel should) give oxygen.
Eye contact	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Keep eye wide open while rinsing. Do not rub affected area. If symptoms persist, call a physician.
Skin contact	Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes. If symptoms persist, call a physician.
Ingestion	Do NOT induce vomiting. Rinse mouth. Never give anything by mouth to an unconscious person. Call a physician or poison control center immediately.
Self-protection of the first aider	Remove all sources of ignition. Ensure that medical personnel are aware of the material(s) involved, take precautions to protect themselves and prevent spread of contamination. Use personal protective equipment as required. See section 8 for more information. Do not use mouth-to-mouth method if victim ingested or inhaled the substance; give artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device. Do not breathe vapor or mist.

Most important symptoms and effects, both acute and delayed

Symptoms	Coughing and/ or wheezing. Difficulty in breathing.
Effects of Exposure	Causes damage to organs.

Indication of any immediate medical attention and special treatment needed

Note to physicians	Treat symptomatically.
---------------------------	------------------------

5. Fire-fighting measures

Suitable Extinguishing Media	Dry chemical. Carbon dioxide (CO2). Water spray. Alcohol resistant foam.
Large Fire	CAUTION: Use of water spray when fighting fire may be inefficient.
Unsuitable extinguishing media	Do not scatter spilled material with high pressure water streams.
Specific hazards arising from the chemical	Risk of ignition. Keep product and empty container away from heat and sources of ignition. In the event of fire, cool tanks with water spray. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.
Explosion data	
Sensitivity to mechanical impact	None.
Sensitivity to static discharge	Yes.
Special protective equipment and precautions for fire-fighters	Firefighters should wear self-contained breathing apparatus and full firefighting turnout gear. Use personal protection equipment.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Personal precautions	Evacuate personnel to safe areas. Use personal protective equipment as required. See section 8 for more information. Avoid contact with skin, eyes or clothing. Ensure adequate ventilation. Keep people away from and upwind of spill/leak. ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Pay attention to flashback. Take precautionary measures against static discharges. All equipment used when handling the product must be grounded. Do not touch or walk through spilled material. Do not breathe vapor or mist.
Other information	Ventilate the area. Refer to protective measures listed in Sections 7 and 8.

Methods and material for containment and cleaning up

Methods for containment	Stop leak if you can do it without risk. Do not touch or walk through spilled material. A vapor suppressing foam may be used to reduce vapors. Dike far ahead of spill to collect runoff water. Keep out of drains, sewers, ditches and waterways. Absorb with earth, sand or other non-combustible material and transfer to containers for later disposal.
Methods for cleaning up	Take precautionary measures against static discharges. Dam up. Soak up with inert absorbent material. Pick up and transfer to properly labeled containers.
Prevention of secondary hazards	Clean contaminated objects and areas thoroughly observing environmental regulations.

7. Handling and storage

Precautions for safe handling

Advice on safe handling	Use personal protection equipment. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Use grounding and bonding connection when transferring this material to prevent static discharge, fire or explosion. Use spark-proof tools and explosion-proof equipment. Keep in an area equipped with sprinklers. Use according to package label instructions. Handle in accordance with good industrial hygiene and safety practice. Avoid contact with skin, eyes or clothing. Do not breathe vapor or mist. In case of insufficient ventilation, wear suitable respiratory equipment. Handle product only in closed system or provide appropriate exhaust ventilation. Do not eat, drink or smoke when using this product. Take off contaminated clothing and wash before reuse.
--------------------------------	---

Conditions for safe storage, including any incompatibilities

Storage Conditions

Keep containers tightly closed in a dry, cool and well-ventilated place. Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric motors and static electricity). Keep in properly labeled containers. Do not store near combustible materials. Keep in an area equipped with sprinklers. Store in accordance with the particular national regulations. Store in accordance with local regulations. Store locked up. Keep out of the reach of children.

8. Exposure controls/personal protection

Control Parameters

Exposure Limits

Chemical name	ACGIH TLV	OSHA PEL	NIOSH
METHANOL 67-56-1	TWA: 200 ppm STEL: 250 ppm pSk	TWA: 200 ppm TWA: 260 mg/m ³ (vacated) TWA: 200 ppm (vacated) TWA: 260 mg/m ³ (vacated) STEL: 250 ppm (vacated) STEL: 325 mg/m ³ Sdv	TWA: 200 ppm; TWA: 260 mg/m ³ ; STEL: 250 ppm STEL: 325 mg/m ³ IDLH: 6000 ppm

Chemical name	Alberta	British Columbia	Ontario	Quebec
METHANOL 67-56-1	TWA: 200 ppm; TWA: 262 mg/m ³ ; STEL: 250 ppm; STEL: 328 mg/m ³ ; pSk	TWA: 200 ppm; STEL: 250 ppm; Sk	TWA: 200 ppm; STEL: 250 ppm; dSk	TWAEV: 200 ppm; TWAEV: 262 mg/m ³ ; STEV: 250 ppm; STEV: 328 mg/m ³ ; Sd

Chemical name	Manitoba	New Brunswick	Newfoundland and Labrador	Nova Scotia
METHANOL	TWA: 200 ppm; STEL: 250 ppm; pSk	TWA: 200 ppm; STEL: 250 ppm; pSk	TWA: 200 ppm; STEL: 250 ppm; pSk	TWA: 200 ppm; STEL: 250 ppm; pSk

Chemical name	Nunavut	Prince Edward Island	Saskatchewan	Yukon
METHANOL	TWA: 200 ppm; STEL: 250 ppm; Sk	TWA: 200 ppm; STEL: 250 ppm;	TWA: 200 ppm; STEL: 250 ppm; pSd	TWA: 200 ppm; TWA: 260 mg/m ³ ; STEL: 250 ppm; STEL: 310 mg/m ³ ; Sk

Biological occupational exposure limits

Chemical name	ACGIH
METHANOL 67-56-1	15 mg/L - urine (Methanol) - end of shift

Appropriate engineering controls

Engineering controls Showers
Eyewash stations
Ventilation systems.

Individual protection measures, such as personal protective equipment

Eye/face protection Tight sealing safety goggles.

Hand protection Wear suitable gloves.

Skin and body protection Wear suitable protective clothing. Antistatic boots. Chemical resistant apron. Wear fire/flame resistant/retardant clothing.

Respiratory protection Use appropriate respiratory protection. Consult with an industrial hygienist to determine the appropriate respiratory protection for your specific use of this material.

General hygiene considerations Do not eat, drink or smoke when using this product. Contaminated work clothing should not be allowed out of the workplace. Regular cleaning of equipment, work area and clothing is recommended. Wash hands before breaks and immediately after handling the product. Avoid contact with skin, eyes or clothing. Do not breathe vapor or mist. Remove and wash contaminated clothing and gloves, including the inside, before re-use.

9. Physical and chemical properties

Information on basic physical and chemical properties

Appearance Colorless to Blue Liquid
Physical state Liquid
Color Colorless to Blue
Odor (includes odor threshold)

<u>Property</u>	<u>Values</u>	<u>Remarks • Method</u>
Melting point / freezing point	- 73 °C / 99.4 °F	
Boiling point (or initial boiling point or boiling range)	64 °C / 147.2 °F	
Flammability (solid, gas)	No data available	
Flammability Limit in Air		
Upper flammability limit:	No data available	
Lower flammability limit:	No data available	
Flash point	11 °C / 51.8 °F	
Autoignition temperature	No data available	
Decomposition temperature	No data available	
SADT (°C)	No data available	
pH	No data available	
pH (as aqueous solution)	No data available	
Kinematic viscosity	No Data Available	
Dynamic viscosity	No data available	
Solubility	No Data Available	
Water solubility	Soluble in water	
Partition coefficient n-octanol/water (log value)	No Data Available	
Vapor pressure (includes evaporation rate)	169.27	
Evaporation rate	Not applicable	
Density and/or relative density	0.792 - 0.821 g/cm3	
Bulk density	No data available	
Density	No data available	

Vapor density	~1.1	Air = 1
Particle characteristics		
Particle Size	No data available	
Particle Size Distribution	No data available	

Other information

10. Stability and reactivity

Reactivity	High temperatures / direct heat.
Chemical stability	Stable under normal conditions.
Possibility of hazardous reactions	Flammable Liquid.
Conditions to avoid	Heat, flames and sparks. Excessive heat.
Incompatible materials	None known based on information supplied.
Hazardous decomposition products	Carbon oxides. Formaldehyde. Thermal decomposition can lead to release of irritating and toxic gases and vapors.

11. Toxicological information

Information on likely routes of exposure

Product Information

Inhalation	Specific test data for the substance or mixture is not available. Toxic by inhalation. (based on components).
Eye contact	Specific test data for the substance or mixture is not available.
Skin contact	Specific test data for the substance or mixture is not available.
Ingestion	Specific test data for the substance or mixture is not available.

Symptoms related to the physical, chemical and toxicological characteristics

Symptoms	No information available.
----------	---------------------------

<u>Acute toxicity</u>	Toxic by inhalation.
-----------------------	----------------------

Numerical measures of toxicity

The following ATE values have been calculated for the mixture

ATEmix (inhalation-gas)	99,999.00 ppm
ATEmix (inhalation-dust/mist)	0.527 mg/L

Unknown acute toxicity

Oral LD50	6889
Dermal LD50	17556
Inhalation LC50	70711 ml/m ³ Vapor Estimated

Component Information

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
METHANOL	= 6200 mg/kg (Rat)	= 15840 mg/kg (Rabbit)	= 22500 ppm (Rat) 8 h

67-56-1			
---------	--	--	--

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritation	No information available.
Serious eye damage/eye irritation	No information available.
Respiratory or skin sensitization	No information available.
Germ cell mutagenicity	No information available.
Carcinogenicity	No information available.
Reproductive toxicity	No information available.
STOT - single exposure	Causes damage to organs.
STOT - repeated exposure	No information available.
Aspiration hazard	No information available.

12. Ecological information

Ecotoxicity	Harmful to aquatic life.
--------------------	--------------------------

Chemical name	Algae/aquatic plants	Fish	Toxicity to microorganisms	Crustacea
METHANOL 67-56-1	-	LC50: =28200mg/L (96h, Pimephales promelas) LC50: >100mg/L (96h, Pimephales promelas) LC50: 19500 - 20700mg/L (96h, Oncorhynchus mykiss) LC50: 18 - 20mL/L (96h, Oncorhynchus mykiss) LC50: 13500 - 17600mg/L (96h, Lepomis macrochirus)	-	-

Persistence and degradability	No information available.
--------------------------------------	---------------------------

Bioaccumulative potential

Component Information

Chemical name	Partition coefficient
METHANOL 67-56-1	-0.77

Other adverse effects No information available.

13. Disposal considerations

Waste treatment methods

Waste from residues/unused products	Should not be released into the environment. Dispose of in accordance with local regulations. Dispose of waste in accordance with environmental legislation.
Contaminated packaging	Empty containers pose a potential fire and explosion hazard. Do not cut, puncture or weld containers.
US EPA Waste Number	U154 D001.
California waste information	This product contains one or more substances that are listed with the State of California as a hazardous waste.

14. Transport information

Note: This information is not intended to convey all specific regulatory information relating to this product. Transportation classifications may vary by container volume and may be influenced by regional or country variations in regulations. It is the responsibility of the transporting organization to follow all applicable laws, regulations and rules relating to the transportation of the material.

DOT

UN number or ID number	UN1230
Proper shipping name	Flammable liquids, n.o.s. (Contains Methanol) Limited Quantity (LQ)
Transport hazard class(es)	3
Subsidiary hazard class	6.1
Packing group	II

IATA

UN number or ID number	UN1230
UN proper shipping name	Flammable liquid, n.o.s. (Contains Methanol) Limited Quantity (LQ)
Transport hazard class(es)	3
Subsidiary hazard class	6.1
Packing group	II

IMDG

UN number or ID number	UN1230
UN proper shipping name	Flammable liquid, n.o.s. (Contains Methanol) Limited Quantity (LQ)
Transport hazard class(es)	3
Subsidiary hazard class	6.1
Packing group	II
EmS-No.	F-E-S--D
Special Provisions	3 - Flammable Liquid

15. Regulatory information

Safety, health and environmental regulations/legislation specific for the substance or mixture

International Regulations

The Montreal Protocol on Substances that Deplete the Ozone Layer Not applicable

The Stockholm Convention on Persistent Organic Pollutants Not applicable

The Rotterdam Convention Not applicable

*Contact supplier for details. One or more substances in this product are either not listed on the US TSCA inventory, listed on the confidential US TSCA inventory or are otherwise exempted from inventory listing requirements

International Inventories

TSCA	Complies
DSL/NDSL	Complies
EINECS/ELINCS	Complies
ENCS	Complies
IECSC	Complies
KECI	Complies
PICCS	Complies
AICS	Complies

Legend:

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory
 DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List
 EINECS/ELINCS - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances
 ENCS - Japan Existing and New Chemical Substances
 IECSC - China Inventory of Existing Chemical Substances
 KECL - Korean Existing Chemicals Inventory
 PICCS - Philippines Inventory of Chemicals and Chemical Substances
 AICS - Australian Inventory of Chemical Substances

US Federal Regulations

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372.

Chemical name	SARA 313 - Threshold Values %
METHANOL - 67-56-1	1.0

Should this product meet EPCRA 311/312 Tier reporting criteria at 40 CFR 370, refer to Section 2 of this SDS for appropriate classifications.

SARA 311/312 Hazard Categories

Acute health hazard	Yes
Chronic Health Hazard	No
Fire hazard	Yes
Sudden release of pressure hazard	No
Reactive Hazard	No

CWA (Clean Water Act)

This product does not contain any substances regulated as pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42).

CERCLA

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302).

Chemical name	Hazardous Substances RQs	Extremely Hazardous Substances RQs	Reportable Quantity (RQ)
---------------	--------------------------	------------------------------------	--------------------------

METHANOL 67-56-1	5000 lb / kg (final RQ)	-	RQ 5000 lb final RQ RQ 2270 kg final RQ
---------------------	----------------------------	---	--

US State Regulations

California Proposition 65

This product contains the following Proposition 65 chemicals:.

Chemical name	California Proposition 65
METHANOL - 67-56-1	Developmental

U.S. State Right-to-Know Regulations

Chemical name	New Jersey	Massachusetts	Pennsylvania
METHANOL 67-56-1	X	X	X

U.S. EPA Label Information

EPA Pesticide Registration Number Not applicable

WHMIS Hazard Class

B2 - Flammable liquid, D1A - Very toxic materials, D2B - Toxic materials

16. Other information

NFPA	Health hazards 2	Flammability 3	Instability 0	Special hazards -
HMIS	Health hazards 2	Flammability 3	Physical hazards 0	Personal protection E

Revision Date 21-Apr-2026

Revision Note No information available.

Disclaimer

Illinois Tool Works Inc. believes the information contained in this data sheet is accurate as of the date compiled. However, Illinois Tool Works Inc. makes no warranty, express or implied, as to the accuracy, reliability or completeness of the information. User is responsible for evaluating whether such information or this product is fit for a particular purpose and suitable for a particular use or application. The information in this data sheet may not be valid if this product is used in combination with other products or in processes for which it was not designed. Illinois Tool Works Inc. disclaims any liability for consequential or incidental damages of any kind, including lost profits, arising from the sale or use of this product. Ensure you have the most current version of this data sheet by contacting us or reviewing our web site.