



SAFETY DATA SHEET

This safety data sheet was created pursuant to the requirements of:
US OSHA Hazard Communication Standard (29 CFR 1910.1200) and Canada WHMIS
2015 which includes the amended Hazardous Products Act (HPA) and the Hazardous
Products Regulation (HPR)

Revision Date 09-Mar-2026

Version 1

1. Identification

Product identifier

Product Name Wynn's Turbo Cleaner 6OZ

Other means of identification

Product Code WN 21650

Synonyms None

Recommended use of the chemical and restrictions on use

Recommended Use See directions provided with product

Restrictions on use All other applications

Details of the supplier of the safety data sheet

Supplier Address

ITW Professional Automotive Products
3606 Craftsman Blvd.
Lakeland, FL 33803

Distributor

Manufacturer Address

May Also Be Distributed by:
Logistic Distribution
550 Industrial Drive
Milton, ON, Canada L9T 5A6

Manufactured and Distributed by:

E-mail address EHS@itwproap.com

Emergency telephone number

Company Phone Number 863-665-3338

24-hour emergency phone number Chem-Tel: 800-255-3924
International Emergency:
00+1+ 813-248-0585
Contract Number: MIS0003583

2. Hazard(s) identification

Classification of the substance or mixture

Aerosols	Category 3
Skin corrosion/irritation	Category 2
Serious eye damage/eye irritation	Category 1
Skin sensitization	Category 1
Carcinogenicity	Category 1B
Aspiration hazard	Category 1

Label elements

**Danger****Hazard statements**

Pressurized container: May burst if heated.
Causes skin irritation.
Causes serious eye damage.
May cause an allergic skin reaction.
May cause cancer.
May be fatal if swallowed and enters airways.

Precautionary Statements - Prevention

Do not handle until all safety precautions have been read and understood.
Wear protective gloves, protective clothing, eye protection and face protection.
Wash face, hands and any exposed skin thoroughly after handling.
Avoid breathing dust, fume, gas, mist, vapors and spray.
Contaminated work clothing should not be allowed out of the workplace.
Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
Do not pierce or burn, even after use.

Precautionary Statements - Response

IF exposed or concerned: Get medical advice/attention.
Specific treatment (see supplemental first aid instructions on this label).

Eyes

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
Immediately call a POISON CENTER or doctor.

Skin

IF ON SKIN: Wash with plenty of water and soap.
Take off contaminated clothing and wash it before reuse.
If skin irritation or rash occurs: Get medical advice and attention.

Ingestion

IF SWALLOWED: Immediately call a POISON CENTER or doctor.
Do NOT induce vomiting.

Precautionary Statements - Storage

Store locked up.
Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

Precautionary Statements - Disposal

Dispose of contents and container in accordance with local, regional, national, and international regulations as applicable.

Unknown acute toxicity

3.753 % of the mixture consists of ingredient(s) of unknown acute oral toxicity.
18.253 % of the mixture consists of ingredient(s) of unknown acute dermal toxicity.
72.981 % of the mixture consists of ingredient(s) of unknown acute inhalation toxicity (vapor).
69.391 % of the mixture consists of ingredient(s) of unknown acute inhalation toxicity (dust/mist).

Hazards classified under paragraph (d)(1)(ii) of 1910.1200

No information available.

Other Information

May be harmful if swallowed. May be harmful in contact with skin. Toxic to aquatic life. Very toxic to aquatic life with long lasting effects.

3. Composition/information on ingredients

Substance

Not applicable.

Mixture

Chemical name	CAS No.	Weight-%	Hazardous Material Information Review Act registry number (HMIRA registry #)	Date HMIRA filed and date exemption granted (if applicable)
Naphtha (petroleum), heavy aromatic	64742-94-5	10-30%	-	-
2-Butoxyethanol	111-76-2	5-10%	-	-
DIPROPYLENE GLYCOL MONOMETHYL ETHER	34590-94-8	3-7%	-	-
Diethylene glycol monobutyl ether	112-34-5	1-5%	-	-
Ammonium hydroxide	1336-21-6	1-5%	-	-
Cocamide diethanolamine	68603-42-9	1-5%	-	-
Naphthalene	91-20-3	1-5%	-	-
Benzene, 1,2,3-trimethyl-	526-73-8	1-5%	-	-
1,2,4-Trimethylbenzene	95-63-6	1-5%	-	-
Cumene	98-82-8	0.1-1%	-	-
Diethanolamine	111-42-2	0.1-1%	-	-

4. First-aid measures

Description of first aid measures

General advice

Immediate medical attention is required. Show this safety data sheet to the doctor in attendance. IF exposed or concerned: Get medical advice/attention.

Inhalation

Remove to fresh air. Aspiration into lungs can produce severe lung damage. If breathing has stopped, give artificial respiration. Get medical attention immediately. Avoid direct contact with skin. Use barrier to give mouth-to-mouth resuscitation. If breathing is difficult, (trained personnel should) give oxygen. Delayed pulmonary edema may occur.

Eye contact

Get immediate medical attention. Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Keep eye wide open while rinsing. Do not rub affected area.

Skin contact

Wash off immediately with soap and plenty of water for at least 15 minutes. Get medical attention if irritation develops and persists.

Ingestion

Rinse mouth. Never give anything by mouth to an unconscious person. Do NOT induce vomiting. ASPIRATION HAZARD IF SWALLOWED - CAN ENTER LUNGS AND CAUSE DAMAGE. If vomiting occurs spontaneously, keep head below hips to prevent aspiration. Get immediate medical attention.

Self-protection of the first aider

Avoid contact with skin, eyes or clothing. Ensure that medical personnel are aware of the material(s) involved, take precautions to protect themselves and prevent spread of contamination. Avoid direct contact with skin. Use barrier to give mouth-to-mouth resuscitation. Use personal protective equipment as required. Avoid breathing vapors or mists. See section 8 for more information.

Most important symptoms and effects, both acute and delayed

Symptoms

Burning sensation. Difficulty in breathing. Coughing and/ or wheezing. Dizziness.

Effects of Exposure May cause cancer.

Indication of any immediate medical attention and special treatment needed

Note to physicians Because of the danger of aspiration, emesis or gastric lavage should not be employed unless the risk is justified by the presence of additional toxic substances.

5. Fire-fighting measures

Suitable Extinguishing Media Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Large Fire CAUTION: Use of water spray when fighting fire may be inefficient.

Unsuitable extinguishing media Do not scatter spilled material with high pressure water streams.

Specific hazards arising from the chemical No information available.

Explosion data

Sensitivity to mechanical impact None.

Sensitivity to static discharge None.

Special protective equipment and precautions for fire-fighters Firefighters should wear self-contained breathing apparatus and full firefighting turnout gear. Use personal protection equipment.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Personal precautions Avoid contact with skin, eyes or clothing. Use personal protective equipment as required. Ensure adequate ventilation. Avoid breathing vapors or mists.

Other information Refer to protective measures listed in Sections 7 and 8.

Methods and material for containment and cleaning up

Methods for containment Prevent further leakage or spillage if safe to do so.

Methods for cleaning up Pick up and transfer to properly labeled containers.

Prevention of secondary hazards Clean contaminated objects and areas thoroughly observing environmental regulations.

7. Handling and storage

Precautions for safe handling

Advice on safe handling Handle in accordance with good industrial hygiene and safety practice. Avoid contact with skin, eyes or clothing. Do not eat, drink or smoke when using this product. Take off contaminated clothing and wash before reuse. Avoid breathing vapors or mists. Ensure adequate ventilation. In case of insufficient ventilation, wear suitable respiratory equipment.

Conditions for safe storage, including any incompatibilities

Storage Conditions Keep containers tightly closed in a dry, cool and well-ventilated place. Store locked up. Keep out of the reach of children. Store away from other materials.

8. Exposure controls/personal protection

Control Parameters

Exposure Limits

Chemical name	ACGIH TLV	OSHA PEL	NIOSH
2-Butoxyethanol 111-76-2	TWA: 20 ppm	TWA: 50 ppm TWA: 240 mg/m ³ (vacated) TWA: 25 ppm (vacated) TWA: 120 mg/m ³ dSk Sdv	TWA: 5 ppm; TWA: 24 mg/m ³ ; IDLH: 700 ppm
DIPROPYLENE GLYCOL MONOMETHYL ETHER 34590-94-8	TWA: 50 ppm	TWA: 100 ppm TWA: 600 mg/m ³ (vacated) TWA: 100 ppm (vacated) TWA: 600 mg/m ³ (vacated) STEL: 150 ppm (vacated) STEL: 900 mg/m ³ dSk Sdv	TWA: 100 ppm; TWA: 600 mg/m ³ ; STEL: 150 ppm STEL: 900 mg/m ³ IDLH: 600 ppm
Diethylene glycol monobutyl ether 112-34-5	TWA: 10 ppm inhalable fraction and vapor	-	-
Naphthalene 91-20-3	TWA: 10 ppm pSk	TWA: 10 ppm TWA: 50 mg/m ³ (vacated) TWA: 10 ppm (vacated) TWA: 50 mg/m ³ (vacated) STEL: 15 ppm (vacated) STEL: 75 mg/m ³	TWA: 10 ppm; TWA: 50 mg/m ³ ; STEL: 15 ppm STEL: 75 mg/m ³ IDLH: 250 ppm
Benzene, 1,2,3-trimethyl- 526-73-8	TWA: 10 ppm	-	TWA: 25 ppm; TWA: 125 mg/m ³ ;
1,2,4-Trimethylbenzene 95-63-6	TWA: 10 ppm	-	TWA: 25 ppm; TWA: 125 mg/m ³ ;
Cumene 98-82-8	TWA: 5 ppm	TWA: 50 ppm TWA: 245 mg/m ³ (vacated) TWA: 50 ppm (vacated) TWA: 245 mg/m ³ dSk Sdv	TWA: 50 ppm; TWA: 245 mg/m ³ ; IDLH: 900 ppm
Diethanolamine 111-42-2	TWA: 1 mg/m ³ inhalable fraction and vapor pSk	(vacated) TWA: 3 ppm (vacated) TWA: 15 mg/m ³	TWA: 3 ppm; TWA: 15 mg/m ³ ;

Chemical name	Alberta	British Columbia	Ontario	Quebec
2-Butoxyethanol 111-76-2	TWA: 20 ppm; TWA: 97 mg/m ³ ;	TWA: 20 ppm;	TWA: 20 ppm;	TWAEV: 20 ppm;
DIPROPYLENE GLYCOL MONOMETHYL ETHER 34590-94-8	TWA: 100 ppm; TWA: 606 mg/m ³ ; STEL: 150 ppm; STEL: 909 mg/m ³ ; pSk	TWA: 50 ppm; STEL: 150 ppm;	TWA: 100 ppm; STEL: 150 ppm; dSk	TWAEV: 100 ppm; TWAEV: 606 mg/m ³ ; STEV: 150 ppm; STEV: 909 mg/m ³ ; Sd
Diethylene glycol monobutyl ether 112-34-5	-	-	TWA: 10 ppm; inhalable fraction and vapor	TWAEV: 10 ppm; inhalable fraction and vapour
Naphthalene 91-20-3	TWA: 10 ppm; TWA: 52 mg/m ³ ; STEL: 15 ppm; STEL: 79 mg/m ³ ; pSk	TWA: 10 ppm; Sk	TWA: 10 ppm; dSk	TWAEV: 10 ppm; Sd

Benzene, 1,2,3-trimethyl- 526-73-8	-	TWA: 10 ppm;	-	-
1,2,4-Trimethylbenzene 95-63-6	-	TWA: 10 ppm;	-	-
Cumene 98-82-8	TWA: 50 ppm; TWA: 246 mg/m ³ ;	TWA: 5 ppm; STEL: 75 ppm;	TWA: 50 ppm;	TWAEV: 5 ppm;
Diethanolamine 111-42-2	TWA: 2 mg/m ³ ; pSk	TWA: 2 mg/m ³ ; Sk	TWA: 1 mg/m ³ ; inhalable fraction and vapor dSk	TWAEV: 1 mg/m ³ ; inhalable fraction and vapour Sd

Chemical name	Manitoba	New Brunswick	Newfoundland and Labrador	Nova Scotia
2-Butoxyethanol	TWA: 20 ppm;	TWA: 20 ppm;	TWA: 20 ppm;	TWA: 20 ppm;
DIPROPYLENE GLYCOL MONOMETHYL ETHER	TWA: 50 ppm;	TWA: 100 ppm; STEL: 150 ppm; pSk	TWA: 50 ppm;	TWA: 50 ppm;
Diethylene glycol monobutyl ether	TWA: 10 ppm; inhalable fraction and vapor	TWA: 10 ppm; inhalable fraction and vapor	TWA: 10 ppm; inhalable fraction and vapor	TWA: 10 ppm; inhalable fraction and vapor
Naphthalene	TWA: 10 ppm; pSk	TWA: 10 ppm; pSk	TWA: 10 ppm; pSk	TWA: 10 ppm; pSk
Benzene, 1,2,3-trimethyl- 1,2,4-Trimethylbenzene	TWA: 10 ppm; TWA: 10 ppm;		TWA: 10 ppm; TWA: 10 ppm;	TWA: 10 ppm; TWA: 10 ppm;
Cumene	TWA: 5 ppm;	TWA: 50 ppm;	TWA: 5 ppm;	TWA: 5 ppm;
Diethanolamine	TWA: 1 mg/m ³ ; inhalable fraction and vapor pSk	TWA: 1 mg/m ³ ; inhalable fraction and vapor pSk	TWA: 1 mg/m ³ ; inhalable fraction and vapor pSk	TWA: 1 mg/m ³ ; inhalable fraction and vapor pSk

Chemical name	Nunavut	Prince Edward Island	Saskatchewan	Yukon
2-Butoxyethanol	TWA: 20 ppm; STEL: 30 ppm;	TWA: 20 ppm;	TWA: 20 ppm; STEL: 30 ppm;	TWA: 50 ppm; TWA: 240 mg/m ³ ; STEL: 150 ppm; STEL: 720 mg/m ³ ; Sk
DIPROPYLENE GLYCOL MONOMETHYL ETHER	TWA: 100 ppm; STEL: 150 ppm; Sk	TWA: 50 ppm;	TWA: 100 ppm; STEL: 150 ppm; pSd	
Diethylene glycol monobutyl ether		TWA: 10 ppm; inhalable fraction and vapor		
Naphthalene	TWA: 10 ppm; STEL: 15 ppm; Sk	TWA: 10 ppm;	TWA: 10 ppm; STEL: 15 ppm; pSd	TWA: 10 ppm; TWA: 50 mg/m ³ ; STEL: 15 ppm; STEL: 75 mg/m ³ ;
Benzene, 1,2,3-trimethyl- 1,2,4-Trimethylbenzene		TWA: 10 ppm; TWA: 10 ppm;		
Cumene	TWA: 50 ppm; STEL: 74 ppm;	TWA: 5 ppm;	TWA: 50 ppm; STEL: 74 ppm;	TWA: 50 ppm; TWA: 245 mg/m ³ ; STEL: 75 ppm; STEL: 365 mg/m ³ ; Sk
Diethanolamine	TWA: 2 mg/m ³ ; STEL: 4 mg/m ³ ; Sk	TWA: 1 mg/m ³ ; inhalable fraction and vapor	TWA: 2 mg/m ³ ; STEL: 4 mg/m ³ ; pSd	

Biological occupational exposure limits

Chemical name	ACGIH
2-Butoxyethanol 111-76-2	200 mg/g creatinine - urine (Butoxyacetic acid with hydrolysis) - end of shift
Naphthalene 91-20-3	- (1-Naphthol with hydrolysis plus 2-Naphthol with hydrolysis) - end of shift

Appropriate engineering controls

Engineering controls	Showers Eyewash stations Ventilation systems.
-----------------------------	---

Individual protection measures, such as personal protective equipment

Eye/face protection	Face protection shield. Tight sealing safety goggles. Wear safety glasses with side shields (or goggles).
Hand protection	Wear suitable gloves.
Skin and body protection	Wear suitable protective clothing. Long sleeved clothing.
Respiratory protection	Use appropriate respiratory protection.
General hygiene considerations	Avoid contact with skin, eyes or clothing. Wear suitable gloves and eye/face protection. Do not eat, drink or smoke when using this product. Wash hands before breaks and immediately after handling the product.

9. Physical and chemical properties**Information on basic physical and chemical properties**

Appearance	Clear Light Amber Liquid
Physical state	Aerosol
Color	Light Amber
Odor (includes odor threshold)	

<u>Property</u>	<u>Values</u>	<u>Remarks • Method</u>
Melting point / freezing point	No data available	
Boiling point (or initial boiling point or boiling range)	No data available	
Flammability (solid, gas)	No data available	
Flammability Limit in Air		
Upper flammability limit:	No data available	
Lower flammability limit:	No data available	
Flash point	NFTB	
Autoignition temperature	No data available	
Decomposition temperature	No data available	
SADT (°C)	No data available	
pH	No data available	
pH (as aqueous solution)	No data available	
Kinematic viscosity	2	
Dynamic viscosity	No data available	
Solubility	No Data Available	
Water solubility	Partially soluble	
Partition coefficient n-octanol/water (log	No Data Available	

value)

Vapor pressure (includes evaporation rate) No Data Available

Evaporation rate Not applicable

Density and/or relative density 0.93

Bulk density No data available

Density No data available

Vapor density No data available

Particle characteristics

Particle Size No data available

Particle Size Distribution No data available

Other information**10. Stability and reactivity**

Reactivity No information available.

Chemical stability Stable under normal conditions.

Possibility of hazardous reactions None under normal processing.

Conditions to avoid Excessive heat.

Incompatible materials Strong acids. Strong bases. Strong oxidizing agents.

Hazardous decomposition products None known based on information supplied.

11. Toxicological informationInformation on likely routes of exposure**Product Information**

Inhalation	Specific test data for the substance or mixture is not available. Aspiration into lungs can produce severe lung damage. May cause pulmonary edema. Pulmonary edema can be fatal. May cause irritation of respiratory tract. Harmful by inhalation. (based on components).
Eye contact	Specific test data for the substance or mixture is not available. Causes serious eye damage. May cause irreversible damage to eyes.
Skin contact	Specific test data for the substance or mixture is not available. Repeated exposure may cause skin dryness or cracking. Causes skin irritation. (based on components).
Ingestion	Specific test data for the substance or mixture is not available. Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea. Potential for aspiration if swallowed. May cause lung damage if swallowed. Aspiration may cause pulmonary edema and pneumonitis. May be fatal if swallowed and enters airways.

Symptoms related to the physical, chemical and toxicological characteristics

Symptoms Redness. Burning. May cause blindness. Difficulty in breathing. Coughing and/ or wheezing. Dizziness. May cause redness and tearing of the eyes.

Acute toxicity Harmful by inhalation.

Numerical measures of toxicity

The following ATE values have been calculated for the mixture

ATEmix (oral)	2,053.50 mg/kg
ATEmix (dermal)	3,295.40 mg/kg
ATEmix (inhalation-gas)	99,999.00 ppm
ATEmix (inhalation-vapor)	99,999.00 mg/l
ATEmix (inhalation-dust/mist)	5.38 mg/l

Unknown acute toxicity

3.753 % of the mixture consists of ingredient(s) of unknown acute oral toxicity
 18.253 % of the mixture consists of ingredient(s) of unknown acute dermal toxicity
 72.981 % of the mixture consists of ingredient(s) of unknown acute inhalation toxicity (vapor)
 69.391 % of the mixture consists of ingredient(s) of unknown acute inhalation toxicity (dust/mist)

Component Information

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
Naphtha (petroleum), heavy aromatic 64742-94-5	> 5000 mg/kg (Rat)	> 2000 mg/kg (Rabbit)	> 590 mg/m ³ (Rat) 4 h
2-Butoxyethanol 111-76-2	= 470 mg/kg (Rat)	> 2000 mg/kg (Rabbit)	= 450 ppm (Rat) 4 h = 486 ppm (Rat) 4 h
DIPROPYLENE GLYCOL MONOMETHYL ETHER 34590-94-8	= 5.35 g/kg (Rat)	= 9500 mg/kg (Rabbit)	-
Diethylene glycol monobutyl ether 112-34-5	= 5660 mg/kg (Rat)	= 2700 mg/kg (Rabbit)	-
Ammonium hydroxide 1336-21-6	= 350 mg/kg (Rat)	-	-
Cocamide diethanolamine 68603-42-9	> 5000 mg/kg (Rat)	> 2 g/kg (Rabbit)	-
Naphthalene 91-20-3	= 1110 mg/kg (Rat)	= 1120 mg/kg (Rabbit)	> 0.4 mg/L (Rat) 4 h
1,2,4-Trimethylbenzene 95-63-6	= 3280 mg/kg (Rat)	> 3440 mg/kg (Rat)	= 18 g/m ³ (Rat) 4 h
Cumene 98-82-8	= 1400 mg/kg (Rat)	= 12300 µL/kg (Rabbit)	> 3577 ppm (Rat) 6 h
Diethanolamine 111-42-2	= 780 mg/kg (Rat)	= 11.9 mL/kg (Rabbit)	> 3.35 mg/L (Rat) 4 h

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritation	Classification based on data available for ingredients. Causes skin irritation.
Serious eye damage/eye irritation	Classification based on data available for ingredients. Causes burns. Causes serious eye damage.
Respiratory or skin sensitization	No information available.
Germ cell mutagenicity	No information available.
Carcinogenicity	Contains a known or suspected carcinogen. Classification based on data available for ingredients. May cause cancer.

The table below indicates whether each agency has listed any ingredient as a carcinogen.

Chemical name	ACGIH	IARC	NTP	OSHA
2-Butoxyethanol 111-76-2	A3 - Confirmed Animal Carcinogen with Unknown Relevance to Humans	Group 3 - Unclassifiable as to carcinogenicity in humans	-	-
Cocamide diethanolamine	-	Group 2B - Possibly	-	Present

68603-42-9		carcinogenic to humans		
Naphthalene 91-20-3	A3 - Confirmed Animal Carcinogen with Unknown Relevance to Humans	Group 2B - Possibly carcinogenic to humans	Reasonably Anticipated To Be A Human Carcinogen	Present
1,2,4-Trimethylbenzene 95-63-6	A4 - Not Classifiable as a Human Carcinogen	-	-	-
Cumene 98-82-8	A3 - Confirmed Animal Carcinogen with Unknown Relevance to Humans	Group 2B - Possibly carcinogenic to humans	Reasonably Anticipated To Be A Human Carcinogen	Present
Diethanolamine 111-42-2	A3 - Confirmed Animal Carcinogen with Unknown Relevance to Humans	Group 2B - Possibly carcinogenic to humans	-	Present

Reproductive toxicity No information available.

STOT - single exposure No information available.

STOT - repeated exposure No information available.

Aspiration hazard May be fatal if swallowed and enters airways.

12. Ecological information

Ecotoxicity Very toxic to aquatic life with long lasting effects. Toxic to aquatic life.

Chemical name	Algae/aquatic plants	Fish	Toxicity to microorganisms	Crustacea
Naphtha (petroleum), heavy aromatic 64742-94-5	-	LC50: =19mg/L (96h, Pimephales promelas) LC50: =2.34mg/L (96h, Oncorhynchus mykiss) LC50: =1740mg/L (96h, Lepomis macrochirus) LC50: =45mg/L (96h, Pimephales promelas) LC50: =41mg/L (96h, Pimephales promelas)	-	EC50: =0.95mg/L (48h, Daphnia magna)
2-Butoxyethanol 111-76-2	-	LC50: =1490mg/L (96h, Lepomis macrochirus) LC50: =2950mg/L (96h, Lepomis macrochirus)	-	EC50: >1000mg/L (48h, Daphnia magna)
DIPROPYLENE GLYCOL MONOMETHYL ETHER 34590-94-8	-	LC50: >10000mg/L (96h, Pimephales promelas)	-	LC50: =1919mg/L (48h, Daphnia magna)
Diethylene glycol monobutyl ether 112-34-5	EC50: >100mg/L (96h, Desmodesmus subspicatus)	LC50: =1300mg/L (96h, Lepomis macrochirus)	-	EC50: >100mg/L (48h, Daphnia magna)
Ammonium hydroxide 1336-21-6	-	LC50: =8.2mg/L (96h, Pimephales promelas)	-	EC50: =0.66mg/L (48h, water flea) EC50: =0.66mg/L (48h, Daphnia pulex)
Cocamide diethanolamine 68603-42-9	-	LC50: =3.6mg/L (96h, Brachydanio rerio)	-	-

Naphthalene 91-20-3	-	LC50: 5.74 - 6.44mg/L (96h, Pimephales promelas) LC50: =1.6mg/L (96h, Oncorhynchus mykiss) LC50: 0.91 - 2.82mg/L (96h, Oncorhynchus mykiss) LC50: =1.99mg/L (96h, Pimephales promelas) LC50: =31.0265mg/L (96h, Lepomis macrochirus)	EC50 = 0.93 mg/L 30 min EC50 > 20 mg/L 18 h	LC50: =2.16mg/L (48h, Daphnia magna) EC50: =1.96mg/L (48h, Daphnia magna) EC50: 1.09 - 3.4mg/L (48h, Daphnia magna)
1,2,4-Trimethylbenzene 95-63-6	-	LC50: 7.19 - 8.28mg/L (96h, Pimephales promelas)	-	EC50: =6.14mg/L (48h, Daphnia magna)
Cumene 98-82-8	EC50: =2.6mg/L (72h, Pseudokirchneriella subcapitata)	LC50: 6.04 - 6.61mg/L (96h, Pimephales promelas) LC50: =4.8mg/L (96h, Oncorhynchus mykiss) LC50: =2.7mg/L (96h, Oncorhynchus mykiss) LC50: =5.1mg/L (96h, Poecilia reticulata)	EC50 = 0.89 mg/L 5 min EC50 = 1.10 mg/L 15 min EC50 = 1.48 mg/L 30 min EC50 = 172 mg/L 24 h	EC50: =0.6mg/L (48h, Daphnia magna) EC50: 7.9 - 14.1mg/L (48h, Daphnia magna)
Diethanolamine 111-42-2	EC50: =7.8mg/L (72h, Desmodesmus subspicatus) EC50: 2.1 - 2.3mg/L (96h, Pseudokirchneriella subcapitata)	LC50: 4460 - 4980mg/L (96h, Pimephales promelas) LC50: 1200 - 1580mg/L (96h, Pimephales promelas) LC50: 600 - 1000mg/L (96h, Lepomis macrochirus)	EC50 = 73 mg/L 5 min EC50 > 16 mg/L 16 h	EC50: =55mg/L (48h, Daphnia magna)

Persistence and degradability No information available.

Bioaccumulation

Component Information

Chemical name	Partition coefficient
Naphtha (petroleum), heavy aromatic 64742-94-5	6.5
2-Butoxyethanol 111-76-2	0.81
DIPROPYLENE GLYCOL MONOMETHYL ETHER 34590-94-8	0.35
Diethylene glycol monobutyl ether 112-34-5	1
Naphthalene 91-20-3	3.4
1,2,4-Trimethylbenzene 95-63-6	3.63
Cumene 98-82-8	3.55
Diethanolamine 111-42-2	-2.46

Other adverse effects No information available.

13. Disposal considerations**Waste treatment methods**

Waste from residues/unused products	Dispose of in accordance with local regulations. Dispose of waste in accordance with environmental legislation.
Contaminated packaging	Do not reuse empty containers.
US EPA Waste Number	U055 U165
California waste information	This product contains one or more substances that are listed with the State of California as a hazardous waste.

14. Transport information**DOT**

UN number or ID number	UN 1950
Proper shipping name	Aerosols, Limited Quantity (LQ)
Transport hazard class(es)	2.2

UN number or ID number	UN 1950
UN proper shipping name	Aerosols, Limited Quantity (LQ)
Transport hazard class(es)	2.2

UN number or ID number	UN 1950
UN proper shipping name	Aerosols Limited Quantity (LQ)
Transport hazard class(es)	2.2

15. Regulatory information**Safety, health and environmental regulations/legislation specific for the substance or mixture****International Regulations**

The Montreal Protocol on Substances that Deplete the Ozone Layer Not applicable

The Stockholm Convention on Persistent Organic Pollutants Not applicable

The Rotterdam Convention Not applicable

International Inventories

TSCA	Complies
DSL/NDSL	Complies
EINECS/ELINCS	Does not comply
ENCS	Complies
IECSC	Complies
KECI	Does not comply
PICCS	Does not comply
AICS	Complies

Legend:

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory
DSL/NDL - Canadian Domestic Substances List/Non-Domestic Substances List
EINECS/ELINCS - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances
ENCS - Japan Existing and New Chemical Substances
IECSC - China Inventory of Existing Chemical Substances
KECL - Korean Existing Chemicals Inventory
PICCS - Philippines Inventory of Chemicals and Chemical Substances
AICS - Australian Inventory of Chemical Substances

US Federal Regulations**SARA 313**

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372.

Chemical name	SARA 313 - Threshold Values %
2-Butoxyethanol - 111-76-2	1.0
Diethylene glycol monobutyl ether - 112-34-5	1.0
Ammonium hydroxide - 1336-21-6	1.0
Naphthalene - 91-20-3	0.1
1,2,4-Trimethylbenzene - 95-63-6	1.0
Cumene - 98-82-8	0.1

Should this product meet EPCRA 311/312 Tier reporting criteria at 40 CFR 370, refer to Section 2 of this SDS for appropriate classifications.

SARA 311/312 Hazard Categories

Acute health hazard	No
Chronic Health Hazard	No
Fire hazard	No
Sudden release of pressure hazard	No
Reactive Hazard	No

CWA (Clean Water Act)

This product contains the following substances which are regulated pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42).

Chemical name	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
Ammonium hydroxide 1336-21-6	1000 lb	-	-	X
Naphthalene 91-20-3	100 lb	X	X	X

CERCLA

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302).

Chemical name	Hazardous Substances RQs	Extremely Hazardous Substances RQs	Reportable Quantity (RQ)
Ammonium hydroxide 1336-21-6	1000 lb / kg (final RQ)	-	RQ 1000 lb final RQ RQ 454 kg final RQ
Naphthalene 91-20-3	100 lb / 1 lb / kg (final RQ) kg (final RQ)	-	RQ 100 lb final RQ RQ 45.4 kg final RQ RQ 1 lb final RQ RQ 0.454 kg final RQ
Cumene 98-82-8	5000 lb / kg (final RQ)	-	RQ 5000 lb final RQ RQ 2270 kg final RQ
Diethanolamine 111-42-2	100 lb / kg (final RQ)	-	RQ 100 lb final RQ RQ 45.4 kg final RQ

US State Regulations

California Proposition 65

This product contains the following Proposition 65 chemicals:.

NonHazardous

Chemical name	California Proposition 65
Cocamide diethanolamine - 68603-42-9	Carcinogen
Naphthalene - 91-20-3	Carcinogen
Cumene - 98-82-8	Carcinogen
Diethanolamine - 111-42-2	Carcinogen

U.S. State Right-to-Know Regulations

Chemical name	New Jersey	Massachusetts	Pennsylvania
Water 7732-18-5	-	-	X
2-Butoxyethanol 111-76-2	X	X	X
DIPROPYLENE GLYCOL MONOMETHYL ETHER 34590-94-8	X	X	X
Diethylene glycol monobutyl ether 112-34-5	X	-	X
Ammonium hydroxide 1336-21-6	X	X	X
Naphthalene 91-20-3	X	X	X
1,2,4-Trimethylbenzene 95-63-6	X	X	X
Cumene 98-82-8	X	X	X
DIETHYLBENZENE 25340-17-4	X	-	-
Diethanolamine 111-42-2	X	X	X
Deionized Water 7732-18-5	-	-	X

U.S. EPA Label Information

EPA Pesticide Registration Number Not applicable

16. Other information

NFPA	Health hazards 3	Flammability 1	Instability 0	Special hazards -
HMIS	Health hazards 3 *	Flammability 1	Physical hazards 0	Personal protection X
Chronic Hazard Star Legend	* = Chronic Health Hazard			

Revision Date 09-Mar-2026

Revision Note No information available.

Disclaimer

Illinois Tool Works Inc. believes the information contained in this data sheet is accurate as of the date compiled. However, Illinois Tool Works Inc. makes no warranty, express or implied, as to the accuracy, reliability or completeness of the information. User is responsible for evaluating whether such information or this product is fit for a particular purpose and suitable for a particular use or application. The information in this data sheet may not be valid if this product is used in combination with other products or in processes for which it was not designed. Illinois Tool Works Inc. disclaims any liability for consequential or incidental damages of any kind, including lost profits, arising from the sale or use of this product. Ensure you have the most current version of this data sheet by contacting us or reviewing our web

site.